

# Single-Phase Encapsulated

## General Purpose

.050 - 1 KVA, 130°C Insulation Class; 1.5 - 25 KVA, 180°C Insulation Class

KVA	Catalog Number	Fig.	Height A (in.)	Width B (in.)	Depth C (in.)	Wiring Diagram	Est. Ship Wgt. (lbs.)
<b>277 Volts – 120/240 Volts 60 Hertz • Taps: 2 – 2.5% FCBN</b>							
.250	411-0041-277	1	6.88	3.33	3.06	S277A	5.6
.500	411-0051-277	2	9.06	5.06	4.59		12.0
1	411-0071-277	2	9.06	5.06	4.59		17.8
2	411-0091-277	3	12.50	6.69	5.34		33.4
3	411-0101-277	3	14.56	7.56	7.15		39.8
5	411-0111-277	3	14.56	7.56	7.15		53.6
7.5	411-0131-277	4	16.12	13.50	8.55		98
10	411-0151-277	4	16.12	13.50	8.55		132
15	411-0161-277	4	21.12	16.50	10.06		195
25	411-0181-277	4	21.12	16.50	10.06		275
<b>600 Volts – 120/240 Volts 60 Hertz • Taps: .050 - 1 KVA None, 1.5 – 25 KVA 4 – 2.5% FCBN</b>							
.050	411-0006-000	1	6.88	3.33	3.06	S600A	2.8
.100	411-0026-000	1	6.88	3.33	3.06		3.5
.150	411-0036-000	1	6.88	3.33	3.06		4.1
.250	411-0046-000	1	6.88	3.33	3.06		5.6
.500	411-0056-000	2	9.06	5.06	4.59		12.0
.750	411-0066-000	2	9.06	5.06	4.59		14.4
1	411-0077-000	2	9.06	5.06	4.59		17.8
1.5	411-0087-000	3	12.50	6.69	5.34		26.8
2	411-0097-000	3	12.50	6.69	5.34		33.4
3	411-0107-000	3	14.56	7.56	7.15		39.8
5	411-0117-000	3	14.56	7.56	7.15	53.6	
7.5	411-0137-000	4	16.12	13.50	8.55	98	
10	411-0157-000	4	16.12	13.50	8.55	132	
15	411-0167-000	4	21.12	16.50	10.06	195	
25	411-0187-000	4	21.12	16.50	10.06	275	



## International

1 KVA, 130°C Insulation Class; 2.0 - 25 KVA, 180°C Insulation Class

KVA	Catalog Number	Fig.	Height A (in.)	Width B (in.)	Depth C (in.)	Wiring Diagram	Est. Ship Wgt. (lbs.)
<b>190/200/208/220 x 380/400/416/440 Volts – 120/240 Volts 50/60 Hertz Electrostatic Shielded</b>							
1	511-0078-055	2	9.06	5.06	4.59	S440A	17.8
2	511-0098-055	3	12.50	6.69	5.34		33.4
3	511-0108-055	3	14.56	7.56	7.15		39.8
5	511-0118-055	3	14.56	7.56	7.15		53.6
7.5	511-0138-055	4	16.12	13.50	8.55		98
10	511-0158-055	4	16.12	13.50	8.55		132
15	511-0168-055	4	21.12	16.50	10.06		195
25	511-0188-055	4	21.12	16.50	10.06		275

Note: Housing dimensions subject to change without notice. Contact factory where dimensions are critical.



# Single-Phase Encapsulated

## Products

- *General Purpose: .050 KVA through 25 KVA\**
- *International: 1 KVA through 25 KVA\**

## Applications

- *For all general loads, indoors or out, including lighting, industrial and commercial applications*
- *Units may be banked for 3-Phase operations*

## Specifications

- *Encapsulated with electrical grade resin*
- *Cores of high quality electrical steel*
- *NEMA 3R-rated enclosures*
- *50/60 Hz operation as noted*
- *International units electrostatically shielded*
- *Heat-applied ASA-61 gray power coat finish*
- **Made in U.S.A.**

## Features, Functions, Benefits

- *Large connection compartment with knockouts for ease of wiring and installation*
- *Quiet operation for installation flexibility*
- *Slotted mounting holes for quick and easy mounting*
- *Convenient wall mount design with lifting hooks above 5 KVA*
- *Permanently affixed wiring diagram*

## Standards

- *Built in accordance with NEMA, ANSI, UL and CSA standards*
- *International units are CE Marked*

## \*Options and Accessories

- *CE Marked units available as custom*
- *Other sizes and voltages available as custom*