


Plug-In Units for Type APD and SD Busway (Not I-LINE® Busway)

Circuit Breaker Plug-In Units

Breaker Frame	Trip Rating Amps	600 Vac 3Ø4W for use on both 3-pole and 3Ø4W Busway		Breaker Frame	Trip Rating Amps	600 Vac 3Ø4W for use on both 3-pole and 3Ø4W Busway	
		Catalog Number	Price ‡			Catalog Number	Price ‡
FA	15	SD75415	\$1483.	KA	125	SD78417	\$3713.
	20	SD75420	1483.		150	SD78418	3713.
	30	SD75430	1483.		175	SD78419	3713.
	40	SD75440	1483.		200	SD78426	3713.
	50	SD75450	1483.		225	SD78427	3713.
	60	SD75460	1483.	LA	250	SD67428	6923.
	70	SD75470	1593.		300	SD67436	6923.
	100	SD75416	1593.		350	SD67438	6923.
				400	SD67446	6923.	

100 Ampere Plug-In Busway



Edgewise Mounted
100 A Plug-In Busway

SQUARE D® 100 ampere plug-in busway is a flexible and economical indoor busway. Typical uses are (a) branch power feeders to panelboards or motors and (b) plug-in busway for small distributed loads. The electrical conductors are plated round aluminum or copper bars supported in a steel housing by molded insulators. All plug-in openings are usable and are polarized. Finish is ANSI-49 medium gray.

Straight Lengths — Available only in lengths listed. Normal mounting position is edgewise with neutral at the top.

Hangers — Busway is UL Listed for 10-foot hanger spacing if mounted edgewise. For flatwise mounting (not UL Listed) order two flatwise hangers for each 10 feet of busway.

Cable Tap Box — Plug-in type rated 100 Amperes.

End Closure — Required at both ends of run.

Outlet Cover — Required to cover opening when plug-in unit is relocated.

Elbows and Tees — Order by catalog number.

Aluminum – Straight Lengths, Fittings, and Accessories

Component	3Ø3W 600 V Max.		3Ø3W + Gnd. 600 V Max.		3Ø4W 277/480 V Max. (600 Vac Max.)		3Ø4W + Gnd. 277/480 V Max. (600 Vac Max.)		1Ø3W 120/240 V		1Ø3W + Gnd. 120/240 V	
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price
Straight Lengths - 10 ft.	AP13	\$271.	AP13G	\$357.	AP14	\$352.	AP14G	\$430.	AP14	\$352.	AP14G	\$430.
- 5 ft.	AP135	173.	AP135G	275.	AP145	227.	AP145G	329.	AP145	227.	AP145G	329.
- 3 ft.	AP133	146.	AP133G	228.	AP143	190.	AP143G	275.	AP143	190.	AP143G	275.
Cable Tap Box (Plug-in 100 A.)	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.
Ground Kit	PGKFA2	33.	PGKFA2	33.	PGKFA2	33.
End Closure	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.
Hangers - Edgewise	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.
- Flatwise	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.
Elbows - Front Outside	AP13LFO	336.	AP13LFOG	372.	AP14LFO	361.	AP14LFOG	405.	AP14LFO	361.	AP14LFOG	405.
- Front Inside	AP13LFI	336.	AP13LFIG	372.	AP14LFI	361.	AP14LFIG	405.	AP14LFI	361.	AP14LFIG	405.
Tees - Front Outside	AP13TFO	423.	AP13TFOG	481.	AP14TFO	465.	AP14TFOG	525.	AP14TFO	465.	AP14TFOG	525.
- Front Inside	AP13TFI	423.	AP13TFIG	481.	AP14TFI	465.	AP14TFIG	525.	AP14TFI	465.	AP14TFIG	525.
Cover	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.

Copper – Straight Lengths, Fittings, and Accessories

Component	3Ø3W 600 V Max.		3Ø3W + Gnd. 600 V Max.		3Ø4W 277/480 V Max. (600 Vac Max.)		3Ø4W + Gnd. 277/480 V Max. (600 Vac Max.)		1Ø3W 120/240 V		1Ø3W + Gnd. 120/240 V	
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price
Straight Lengths - 10 ft.	CP13	\$477.	CP13G	\$626.	CP14	\$613.	CP14G	\$752.	CP14	\$613.	CP14G	\$752.
- 5 ft.	CP135	320.	CP135G	395.	CP145	392.	CP145G	483.	CP145	392.	CP145G	483.
- 3 ft.	CP133	267.	CP133G	313.	CP143	319.	CP143G	390.	CP143	319.	CP143G	390.
Cable Tap Box (Plug-in 100 A.)	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.	PTB14	246.
Ground Kit	PGKFA2	33.	PGKFA2	33.	PGKFA2	33.
End Closure	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.	ACP1EC	56.
Hangers - Edgewise	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.	HP1E	25.
- Flatwise	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.	HP1F	25.
Elbows - Front Outside	CP13LFO	512.	CP13LFOG	593.	CP14LFO	548.	CP14LFOG	621.	CP14LFO	548.	CP14LFOG	621.
- Front Inside	CP13LFI	512.	CP13LFIG	593.	CP14LFI	548.	CP14LFIG	621.	CP14LFI	548.	CP14LFIG	621.
Tees - Front Outside	CP13TFO	624.	CP13TFOG	697.	CP14TFO	628.	CP14TFOG	736.	CP14TFO	628.	CP14TFOG	736.
- Front Inside	CP13TFI	624.	CP13TFIG	697.	CP14TFI	628.	CP14TFIG	736.	CP14TFI	628.	CP14TFIG	736.
Outlet Cover	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.	ACP1OC	25.

Plug-In Units

Circuit Breaker Enclosures and Accessories

Enclosure Only (Price Circuit Breaker Separately)	1Ø3W & 3Ø4W ▲		Ground Kit		Floor Operator Attachment	
	Catalog No.	Price	Catalog No.	Price	Catalog No.	Price
QO Breaker—70 A Enclosure	PINQO	\$104.	PGKQO2	\$33.	P11QO	\$72.
QO Breaker/Recpt.—70 A Enclosure ■	PINQOR	162.	PGKQOR	33.	P11QO	72.
FA Breaker—15-100 A Enclosure	PIN100FA	345.	PGKFA2	33.	P11FA	72.

▲ With PIN-QO, use breakers QO215H, QO220H and QO230H. For higher ratings, use FA enclosures and breakers.
 ■ Enclosure with space for three QO circuit breaker poles and provisions for three duplex receptacles.

For additional information, reference Catalog 5600CT9101R12/99 or D-FAX™ #1667, 1668, 1735



+PE7	PE8
------	-----