

All-In-Ones

- Ring or Ringless Type Meter Socket designs available
- UL Listed, Suitable Only for use as Service Equipment
- Meets EUSERC Standards
- Service Disconnect(s) are supplied "Factory Installed"
- Semiflush-REVERSE design available, supplied with Load Center (Indoor Access)
- Supplied with 100% Branch Neutrals, all unused terminals may be used for equipment grounding wires.
- Meets Federal Specification W-P-115c as Type 1, Class 2

RING TYPE	Ampere Rating	By-pass Type	Service (Type of Feed) UL & EUSERC	Short Circuit Current Rating	Catalog Number	List Price (DE3A)	Service Disconnect(s)			Load Center & Branch Circuit Breakers (Order separately pages 1-2, 1-3 or 1-10)			Hub Type (Order Separately page 1-18)	Line Side Main Lugs AGW/kcmil (Al/Cu)	Service Ground Lug AWG/kcmil (Al/Cu)	Weight Each (Lbs) and Pallet Qty.	
							2-Pole Circuits (Max.)	Type (Factory Installed)	Ampere Rating (Max.)	Max. Quantity		Ampere Rating (Max.)					
										Spaces	Circuits						Tandems
RINGLINE	Surface Mount only																
	100	None	OH/UG	10K	SC1624M100S	\$ 451.	1	HOM2100	100	16	24	8	100	A	#6-2/0	#12-1/0	28, 32
	125	None	OH/UG	10K	SC1624M125S	920.	1	HOM2125	125	16	24	8	125†	A	#6-2/0	#12-1/0	28, 32
	200	None	OH/UG	10K	SC2040M200C ☆	1013.	1	HOM2200	200	20	40	20	100	A or B300	#6-300	#12-1/0	47, 18
	Semiflush Mount only																
	100	None	UG	10K	SC1624M100F	\$ 451.	1	HOM2100	100	16	24	8	100	A or B300	#6-2/0	#12-1/0	39, 24
	125	None	UG	10K	SC1624M125F	920.	1	HOM2125	125	16	24	8	110	A or B300	#6-2/0	#12-1/0	39, 24
	200	None	UG	10K	SU2040M200F	1013.	1	HOM2200	200	20	40	20	100	A or B300	#6-300	#12-1/0	47, 18
					SU3040M200F	1251.	1	QOM2200VH	200	30	40	10	110	A or B300	#6-300	#12-1/0	60, 18
	225	None	UG	10K	SU3040M225F	1382.	1	QOM2225VH	225	30	40	10	110	A or B300	#6-300	#12-1/0	60, 18
	Surface Mount only																
	100	None	OH	10K	SO1020M100S	\$ 268.	1	HOM2100	100	10	20	10	80	A	#6-1	#14-4	20, 42
	200	None	OH	22K	SO2040M200S	704.	1	QOM2200VH	200	20	40	20	100	A	#6-350	#8-2/0	43, 21
	200	None	OH/UG	10K	SC3040M200RS	1218.	1	HOM2200	200	30	40	10	125	A or B300	#4-300	#12-1/0	52, 14
					SC40M200S	1474.	1	HOM2200	200	40	40	0	125	A or B300	#6-300	#12-4	60, 14
REVERSE All-In-One - Semiflush Mount with Service Disconnect (outdoor access) and Load Center (indoor access)																	
200	None	UG	10K	SU3040M200R	\$1347.	1	QOM2200VH	200	30	40	10	110	A or B300	#6-300	#12-1/0	60, 15	
225	None	UG	10K	SU3040M225R	1604.	1	QOM2225VH	225	30	40	10	110	A or B300	#6-300	#12-1/0	60, 15	
Surface Mount, convertible to Semiflush with SU400F flange kit (order separately)																	
300	Class 320 None	UG	10K or 22/10K ▼	SU3040D300N ★■	\$2309.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6	
						1	Q2M2100VH	100					
400	Class 320 None	UG	10K or 22/10K ▼	SU3040D400N ★■	4965.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6	
						1	Q2M2200VH	200					
RINGLESS	Surface Mount Only																
	100	Horn	OH/UG†	22K	RC2040M100CH●	1038.	1	QOM2100VH	100	20	40	20	100	A	#6-350	#12-2/0	40, 21
	125	None	OH/UG†	22K	RC2040M125C●♦	970.	1	QOM2125VH	125	20	40	20	100	A	#6-350	#12-2/0	40, 21
		Horn	OH/UG†	22K	RC2040M125CH●	970.	1	QOM2125VH	125	20	40	20	100	A	#6-350	#12-2/0	40, 21
	150	None	OH/UG†	22K	RC2040M150C●♦	1038.	1	QOM2150VH	150	20	40	20	100	A	#6-350	#12-2/0	40, 21
		Horn	OH/UG†	22K	RC2040M150CH●	1038.	1	QOM2150VH	150	20	40	20	100	A	#6-350	#12-2/0	40, 21
	200	None	OH/UG†	22K	RC2040M200C●	1038.	1	QOM2200VH	200	20	40	20	100	A	#6-350	#12-2/0	40, 21
		Horn	OH/UG†	22K	RC2040M200CH●	1038.	1	QOM2200VH	200	20	40	20	100	A	#6-350	#12-2/0	40, 21
	All-In-One Surface Mount, convertible to Semiflush with SU400F flange kit (order separately)																
	300	Class 320 Lever	UG	10K or 22/10K ▼	SU3040D300L ★	\$2309.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6
							1	Q2M2100VH	100				
	400	Class 320 Lever	UG	10K or 22/10K ▼	SU3040D400L ★	4965.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6
							1	Q2M2200VH	200				
	300	K-4 Bolt-On None	UG	10K or 22/10K ▼	SU3040D300K ★♦	2309.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6
							1	Q2M2100VH	100				
400	K-4 Bolt-On None	UG	10K or 22/10K ▼	SU3040D400K ★	4965.	1	Q2M2200VH	200	30	40	10	70 A Max. (22/10K) 80-110 A Max. (10K)	A-L	(2) Studs	#4-250	104, 6	
						1	Q2M2200VH	200					
QO	Surface Mount Only																
	125	Horn	OH/UG†	22K	QC2040M125CH●♦	1140.	1	QOM2125VH	125	20	40	20	100	A	#6-350	#12-1/0	40, 21
	150	Horn	OH/UG†	22K	QC2040M150CH●	1140.	1	QOM2150VH	150	20	40	20	100	A	#6-350	#12-1/0	40, 21
	200	None	OH/UG†	22K	QC2040M200C●	1140.	1	QOM2200VH	200	20	40	20	100	A	#6-350	#12-1/0	40, 21
	Horn	OH/UG†	22K	QC2040M200CH●	1140.	1	QOM2200VH	200	20	40	20	100	A	#6-350	#12-1/0	40, 21	

★ Knockout provided in cover for use with Barrel Lock Kit, order catalog number SCBRLLOCK (see Accessories page 1-18).
 ■ For use only on 120/240 Vac, 1-Phase, 3-Wire system (4-jaw meter socket).
 ▼ UL Listed 10K RMS Symmetrical Amperes Short Circuit Current Rating with 80-110 A maximum branch circuit breakers installed, UL Listed 22/10K RMS Symmetrical Amperes Short Circuit Current Rating with 70 A maximum branch circuit breakers installed.
 † Device not EUSERC approved.
 ● Device supplied with barrel lock provisions factory installed.
 ♦ 125 A HOMELINE 2-Pole breaker can be installed in top position only. All other positions are limited to 100 A max.
 ♦ Order only.
 ☆ Convertible to semiflush with SC200F flange kit (order separately).



Combination Service Entrance Devices

Rainproof – Single Phase, Meter-Mains
Class 4119/4120

Square D

www.squared.com

FOR CURRENT INFORMATION

Meter-Mains

- Meets Federal Specification W-P-115c as Type 1, Class 2
- 120/240 Vac, 1-Phase, 3-Wire, NEMA Type 3R enclosure.
- UL Listed, suitable only for use as service equipment.

LOAD CENTERS

RING TYPE	Ampere Rating	By-pass Type	Service (Type of Feed)		Short Circuit Current Rating	Catalog Number	List Price (DE3A)	Service Disconnect(s)			Load Center, and Branch Circuit Breakers (Order separately pages 1-2, 1-3 or 1-10)			Hub Type (Order separately from page 1-18)	Line Side Main Lugs AWG/kcmil (Al/Cu)	Service Ground Lug AWG/kcmil (Al/Cu)	Weight Each (Lbs) and Pallet Qty.	
			UL	UL & EUSERC				2-Pole Circuits (Max.)	Type (Order Separately from page 1-18 except as noted)	Ampere Rating (Max.)	Max. Quantity							
											Spaces	1-Pole Circuits	Tandems					Ampere Rating (Max.)
RING TYPE	Surface Mount only																	
	100	None	OH/UG	...	10k	CQRB100	\$ 353.	1	QOM100▽■	125	B	#4-1/0	#8-1/0	15, 54
	125	None	OH/UG	...	10k	C125RB	223.	1	QOM1-VH	125	B	#4-1/0	#8-1/0	15, 54
	200	None	OH/UG	...	22k	CQRB200†	922.	1	QOM2200VH■	200	B	#4-250	(2) #8-2/0	26, 24
			OH/UG	...	22k	C200RB	619.	1	QOM2-VH	200	B	#4-250	(2) #8-2/0	26, 24
			OH/UG	...	22k	C2M200RB	656.	1	QOM2-VH QO-VH	200 50	B	#4-250	(2) #8-2/0	27, 20
			OH/UG	...	10k	C4L200RB	693.	2	QO	100	B	#4-250	(2) #8-2/0	27, 28
	Surface Mount, convertible to Semiflush with SU400F flange kit (order separately)																	
	400	Class 320 None	UG	UG	22k	CU12L400N□★	2309.	1 4	Q2L2200H■ Q2L-H QO-VH	200 200 100	A-L	(2) Studs	#4-250	96, 6
	400	Test Block Class 320	UG	...	22k	CU12L400B□★	2415.	1 4	Q2L2200H■ Q2L-H QO-VH	200 200 100	A-L	(2) Studs	#4-250	96, 6
HOMELINE	Surface Mount only																	
	125	None	OH/UG	OH/UG	10k	SC8L125S	513.	4	HOM	125	A	#6-2/0	#12-1/0	27, 32
	200	None	OH/UG	OH/UG	10k	SC12L200C†	860.	6	HOM	100	A or B300	#6-300	#12-1/0	45, 18
	Semiflush Mount only																	
	125	None	OH/UG	OH/UG	10k	SC8L125F	513.	4	HOM	125	A	#6-2/0	#12-1/0	38, 24
	200	None	OH/UG	OH/UG	10k	SC12L200F	860.	6	HOM	100	A or B300	#6-300	#12-1/0	45, 18
	Surface Mount, convertible to Semiflush with SC200F flange kit (order separately) Supplied with Feed Thru Lugs and provisions for Branch Circuit Breakers																	
	200	None	OH/UG	OH/UG	10k	SC816F150C◆	719.	1	HOM2150■	150	8	16	8	100	A or B300	#6-300	#12-1/0	48, 18
						SC816D150C◆	757.	1	HOM2150■	150	8	16	8	100				
						SC816F200C◆	719.	1	HOM2200■	200	8	16	8	100				
SC816D200C◆						757.	1	HOM2200■	200	8	16	8	100					
RINGLESS	Surface Mount Only																	
	200	None	OH/UG	22k	QC12L200C●	946.	6	QO-VH	100	A	#6-350	#12-2/0	40, 21
	200	Horn	OH/UG	22k	QC12L200CH●△▽	1141.	6	QO-VH	100	A	#6-350	#12-2/0	40, 21
	Surface Mount Only, Supplied with Feed Thru Lugs and provisions for Branch Circuit Breakers																	
	100	Horn	OH/UG	22k	QC816F100CH●◆△	822.	1	QOM2100VH■	100	8	16	8	100	A	#6-350	#12-2/0	40, 21
						QC816F125C●◆	790.	1	QOM2125VH■	125	8	16	8	100				
						QC816F125CH●◆△	822.	1	QOM125VH■	125	8	16	8	100				
						QC816F150C●◆	790.	1	QOM2150VH■	150	8	16	8	100				
						QC816F150CH●◆△	822.	1	QOM2150VH■	150	8	16	8	100				
						QC816F200C●◆	822.	1	QOM2200VH■	200	8	16	8	100				
200	Horn	OH/UG	22k	QC816F200CH●◆△	822.	1	QOM2200VH■	200	8	16	8	100	A	#6-350	#12-2/0	40, 21	
					QC816F100CH●◆△	822.	1	QOM2100VH■	100	8	16	8	100					
					QC816F125CH●◆△	822.	1	QOM125VH■	125	8	16	8	100					
					QC816F150CH●◆△	822.	1	QOM2150VH■	150	8	16	8	100					
					QC816F200CH●◆△	822.	1	QOM2200VH■	200	8	16	8	100					
					QC816F150CH●◆△	822.	1	QOM2150VH■	150	8	16	8	100					
Surface Mount, convertible to Semiflush with SU400F flange kit (order separately)																		
400	Class 320 Lever	UG	UG	22k	CU12L400L★	2309.	1 4	Q2L2200H■ Q2L-H QO-VH	200 200 100	A-L	(2) Studs	#4-250	96, 6	
HOMELINE	Surface Mount Only																	
	125	None	OH/UG	OH/UG	10k	RC8L125S	513.	4	HOM	125	A	#6-2/0	#12-1/0	27, 32
	200	None	OH/UG	10k	RC12L200C●	860.	6	HOM	100	A	#6-350	#12-2/0	40, 21
	200	Horn	OH/UG	10k	RC12L200CH●△▽	860.	6	HOM	100	A	#6-350	#12-2/0	40, 21
	Surface Mount Only, Supplied with Feed Thru Lugs																	
	100	Horn	OH/UG	22k	RC816F100CH●◆△	744.	1	QOM2100VH■	100	8	16	8	100	A	#6-350	#12-2/0	40, 21
						RC816F125CH●◆△	744.	1	QOM2125VH■	125	8	16	8	100				
						RC816F150C●◆	719.	1	QOM2150VH■	150	8	16	8	100				
						RC816F150CH●◆△	744.	1	QOM2150VH■	150	8	16	8	100				
						RC816F200C●◆	744.	1	QOM2200VH■	200	8	16	8	100				
RC816F200CH●◆△						744.	1	QOM2200VH■	200	8	16	8	100					

■ Service Disconnect Supplied Factory Installed.
 □ For use only on 120/240 Vac, 1-Phase, 3-Wire system.
 ▽ Supplied with horn bypass and 5th. Jaw factory installed.
 ▽ Order Type QOM1-VH replacement circuit breaker (10k).
 ★ Knockout provided in cover for use with Barrel Lock Kit, order catalog number SCBRLOCK (see Accessories page 1-18).
 ● Device supplied with Barrel Lock provisions factory installed.
 ◆ Supplied with load side feed thru lugs, for #4 AWG-250 kcmil (Al/Cu) conductors.
 † Convertible to semiflush with SC200F flange kit (order separately).
 ● 125 A HOMELINE 2-Pole circuit breaker can be installed in top position only. All other positions are limited to 100 A max.
 ▼ Not stocked in PDS, contact Lexington for delivery.
 ‡ Consumer product only (same as C200RB).

Combination Service Entrance Devices

Circuit Breakers, Accessories

Class 4119/4120

Square D

www.squared.com

FOR CURRENT INFORMATION

Circuit Breakers

For use with Meter Mains and All-In-One devices

Ampere Rating ■	Type: HOM, 1-Pole		Type: HOM, 2-Pole		Type: QO, 1-Pole		Type: QO, 2-Pole		Type: QO-VH, 1-Pole		Type: QO-VH, 2-Pole	
	Catalog Number	Price (DE3D)	Catalog Number	Price (DE3D)	Catalog Number	Price (DE2A)	Catalog Number	Price (DE2A)	Catalog Number	Price (DE2A)	Catalog Number	Price (DE2A)
10	QO110	\$19.40
15	HOM115	\$17.50	QO115	19.40	QO115VH	\$40.30
20	HOM120	17.50	QO120	19.40	QO120VH	40.30
25	HOM125	17.50	QO125	19.40	QO125VH	46.20
30	HOM130	17.50	HOM230	\$ 40.30	QO130	19.40	QO230	\$ 44.70	QO130VH	46.20	QO230VH	\$ 92.00
35	HOM235	40.30	QO135	19.40	QO235	44.70
40	HOM140	17.50	HOM240	40.30	QO140	19.40	QO240	44.70	QO240VH	92.00
45	HOM245	40.30	QO145	19.40	QO245	44.70
50	HOM150	17.50	HOM250	40.30	QO150	19.40	QO250	44.70	QO250VH	92.00
60	HOM260	40.30	QO160	19.40	QO260	44.70	QO260VH	92.00
70	HOM270	82.00	QO170	44.70	QO270	89.00	QO270VH	142.00
80	HOM280	112.00	QO280	126.00	QO280VH	200.00
90	HOM290	112.00	QO290	126.00	QO290VH	200.00
100	HOM2100	112.00	QO2100	126.00	QO2100VH	200.00
Ampere Rating ■	Type: QOM1-VH, 2-Pole			Type: QOM2-VH, 2-Pole			Type: Q2L-H, 2-Pole					
	Catalog Number	Price (DE3A)		Catalog Number	Price (DE3A)		Catalog Number	Price (DE2A)				
50	QOM50VH▲	\$ 89.00					
60	QOM60VH	89.00					
70	QOM70VH	89.00					
80	QOM80VH	128.00					
90	QOM90VH	128.00					
100	QOM100VH	128.00		QOM2100VH	\$297.00		Q2L2100H	\$726.00				
110	QOM110VH	297.00			Q2L2110H	726.00				
125	QOM125VH	297.00		QOM2125VH	297.00		Q2L2125H	726.00				
150		QOM2150VH	297.00		Q2L2150H	726.00				
175		QOM2175VH	297.00		Q2L2175H	726.00				
200		QOM2200VH	297.00		Q2L2200H	726.00				
225		QOM2225VH	297.00					

- Do not exceed mains rating of device
- ▲ Reference National Electrical Code Article 230-79.

Accessories

Description	Catalog Number	Price	Disc. Sch.
Generator Kit: Interlocks main service disconnect and generator circuit breaker (order separately). For use on: HOMELINE CSED Devices RC816F-, RC2040M-QO CSED Devices QC816F-, QC2040M-	RCGK2	\$148.00	(DE3A)
Fifth Jaw Kit for: Meter Main Types: C, RC, SC, QC All-In-One Types: SC, SU (100-225A), QC, RC	5J	11.60	(DE3A)
Fifth Jaw Kit (9:00 position) for: CU12L400L, SU3040D300L, and SU3040D400L	35815SPL	38.50	(DE3A)
Bypass (Horn Type) for: Ringless Type Meter Mains and All-In-Ones (100-200 A)	RCHB2	58.00	(DE3A)
Lexan Meter Socket Cover Plate for: Ring and Ringless Type Meter Mains Ring and Ringless Type All-In-Ones	29007	6.40	(DE4)
Meter Socket Sealing Rings for Ring Type Meter Mains and All-In-Ones: Screw Type Aluminum Snap Type Stainless Steel Latch Type Stainless Steel	29008W 29209-100-02▼ 29008G	12.80 10.60 12.80	(DE4)
Trim Kit for 2" X 6" stud wall, used with: REVERSE All-In-Ones, SU3040M200R, and SU3040M225R	SU2X6TRIM	161.00	(DE3A)
Barrel Lock Kit (Barrel Lock not included), supplied with bracket and mounting screw, refer to listings for where used.	SCBRLLOCK	32.10	(DE3A)
Semiflush Flange Kit for: Ring Type Convertible Surface/Semiflush Meter Mains (125-200 A) All-In-Ones (125-200 A) Ringless Type Convertible Surface/Semiflush Meter Mains (125-200 A)	SC200F	19.30	(DE3A)
Semiflush Flange Kit for: Ring Type Convertible Surface/Semiflush Meter Mains (300-400 A) All-In-Ones (300-400 A) Ringless Type Convertible Surface/Semiflush All-In-Ones (300-400 A)	SU400F	119.00	(DE3A)
Ringless Type Utility Cover for use on: SU3040D300L, SU3040D400L, and CU12L400L. Includes one piece meter socket and pull box cover with handles and closing plate.	C400L	161.00	(DE3A)
Lug Kit includes (4) lugs, for use with #2 AWG-600 kcmil Al/Cu conductors. Lugs are for standard 2-Hole mounting. Meter Main and All-In-One units supplied with (2) Studs per phase and neutral will accept one lug per phase and neutral	CMECLK4	87.00	(DE4A)

▼ Order only. Not stocked in PDS. Order Point: Lexington.

Accessories

Description	Catalog Number	Price	Disc. Sch.
Touch-Up Paint (ASA49 Gray)	PK49SP	\$24.80	(DE1)
Ground Bar Kit QC, SC, RC, and SU (100-225 A) SC3040M200RS and SC40M200S	PK15GTA PK23GTA	10.90 13.50	(DE3A) (DE3A)
Filler Plate for: Meter Main Types: QC, CU All-In-One Types: QC	QOFP	2.30	(DE3A)
Filler Plate for: Meter Main Types: RC, SC All-In-One Types: SC, RC, SU	HOMFP	2.00	(DE3A)
Neutral Lug (#6-2/0) for: Meter Main Types: RC, SC, QC All-In-One Types: SC, SU, QC, RC	LK100AN	6.90	(DE3A)

Hubs and Closing Plates

Hub Series	Conduit Size (inches)	Catalog Number	List Price	Disc. Sch.
Closing Plate for "A" Hub opening		ACP	\$ 8.50	(DE4)
A	1.00	A100	21.50	(DE4)
	1.25	A125	21.50	(DE4)
	1.50	A150	21.50	(DE4)
	2.00	A200	30.40	(DE4)
	2.50	A250	38.50	(DE4)
Adapter plate to allow use of "A" Hubs on "A-L" size hub openings		AAP	21.40	(DE4)
Closing Plate for "A-L" Hub opening		ACPL	11.60	(DE4)
A-L	2.00	A200L ☆	52.00	(DE4)
	2.50	Order A250 + AAP
	3.00	A300L	70.00	(DE4)
	3.50	A350L	72.00	(DE4)
Closing Plate for "B" Hub opening		BCAP	2.40	(DE1A)
B	0.75	B075	22.20	(DE1A)
	1.00	B100	22.20	(DE1A)
	1.25	B125	22.20	(DE1A)
	1.50	B150	22.20	(DE1A)
	2.00	B200	40.90	(DE1A)
	2.50	B250	68.00	(DE1A)
B300	3.00	B300	124.00	(DE1A)

☆ Supplied with AAP adapter plate and "A" hub

DE1	DE1A	DE2A	DE3A	DE3D	DE4	DE4A
-----	------	------	------	------	-----	------



